


GM-B

SELF-DRILLING
MONTAGE SCREW



PRODUCT DESCRIPTION


Drilling, self-tapping montage screws made of surface-hardened carbon steel, electroplated, with a drilling point, fine thread, and a 12 mm flat head with PH2 slot.

APPLICATION



Designed for mounting very thin steel parts and plastic components to steel profiles (up to 2.25 mm), and also for overlap joints of these components.

Protected with paint coating - polyester thickness of not less than 50 µm, intended for use in environments with corrosivity class C1, C2 and C3 according to PN-EN ISO 12944-2: 2001 standard.

Galvanized without paint coating intended for use in environments with corrosivity class C1.



LENGTH OF SCREWS

Fastener type		Dimensions D x L [mm]	Maximum drill capacity [mm]	Maximum thickness of fixed elements [mm]	
			DC	MTmax	
GM-B	NA	4,2 x 13	2,25	2	
GM-B	NA	4,2 x 16	2,25	5	
GM-B	NA	4,2 x 19	2,25	8	
GM-B	NA	4,2 x 25	2,25	14	
GM-B	NA	4,2 x 32	2,25	21	
GM-B	NA	4,2 x 40	2,25	29	
GM-B	NA	4,2 x 65	2,25	54	

The working length of the connector is calculated from the maximum thickness of the DC substrate

NATIONAL TECHNICAL ASSESSMENT ITB-KOT-2018/0680

CHARACTERISTIC BEARING CAPACITY OF SHEAR AND PULL-OUT FIXINGS FROM STEEL SUBSTRATE

Thickness of substrate ¹⁾ [mm]		0,50	0,55	0,63	0,75	0,88	1,00	Wood class \geq C24	
$M_{t,nom}$		8 Nm							
Thickness of steel substrate ²⁾ [mm]	Characteristic capacity For shear [kN]	0,50	0,92	0,92	0,92	—	—	—	/
		0,55	0,92	0,92	0,92	—	—	—	
		0,63	1,32	1,32	1,32	—	—	—	
		0,75	—	—	—	—	—	—	
		0,88	—	—	—	—	—	—	
		1,00	—	—	—	—	—	—	
	For pull-out [kN]	0,50	0,63	0,63	0,63	—	—	—	
		0,55	0,63	0,63	0,63	—	—	—	
		0,63	0,63	0,63	0,63	—	—	—	
		0,75	—	—	—	—	—	—	
		0,88	—	—	—	—	—	—	
		1,00	—	—	—	—	—	—	

¹⁾ steel grade S280GD, S320GD or S350GD according to PN-EN 10346:2015

²⁾ steel grade S280GD, S320GD or S350GD according to PN-EN 10346:2015

If both elements I and II are made of steel grade S320GD, values $V_{R,k}$ can be increased by 8,3%

If both elements I and II are made of steel grade S350GD, values $V_{R,k}$ can be increased by 16,6%

OTHER FEATURES

SUBSTRATE MATERIAL:	PLATE
DIAMETER OF FLAT HEAD:	12 mm
TYPE OF CUT:	PH2
MAXIMUM CAPACITY OF DRILLING:	2,25 mm
THICKNESS OF ZINC COATING:	5 μ m
CORROSIVE ENVIRONMENT:	C1 / C3 (powder.coat)
OPINION ON ANTI-CORROSIVE PROTECTION:	02248/16/Z00NZM
POSSIBILITY OF PAINTING:	YES
PAINT COATING THICKNESS:	50 μ m
RECOMMENDED ROTARY SPEED (IDLE):	1800 rpm



KDWU



ZKP



SZU