


GT F2 P

FARMER SCREWS WITHOUT WASHER
FOR ROOFING PANELS




PRODUCT DESCRIPTION

Self-drilling and tapping carbon steel screws, surface-hardened, electrogalvanized, with reduced drilling point, thread for wood and hex head 6mm.


APPLICATION

Designed for fastening profiled metal sheets of roof tiles to wooden structures.

Protected with paint coating - polyester thickness not less than 50 µm, intended for environments with corrosivity classes C1, C2 and C3 according to PN-EN ISO 12944-2: 2001 standard. Galvanized without paint coating intended for use in environments with atmospheric corrosivity categories C1, C2.



LENGTH OF SCREWS

Fastener type		Dimensions D x L [mm]	Maximum drill capacity [mm]	Maximum thickness of fixed elements [mm]
			DC	MTmax
GT F2 P	NA	4,8 x 35	2 x 1,00	15

The working length of the fastener is calculated from the maximum thickness of the DC substrate

OTHER FEATURES

BASE MATERIAL:	WOOD
SIZE OF HEX HEAD:	6 mm
MINIMUM THICKNESS OF STEEL BASE:	2 x 0,50 mm
MAXIMUM CAPACITY OF DRILLING:	2 x 1,00 mm
THICKNESS OF ZINC COATING:	20 µm
CORROSIVE ENVIRONMENT:	PAINTED - C3 UNPAINTED - C2
OPINION ON ANTI-CORROSIVE PROTECTION:	02248/16/Z00NZM
POSSIBILITY OF PAINTING:	YES
PAINT COATING THICKNESS:	50 µm
TIGHTENING TORQUE:	3 Nm
RECOMMENDED ROTARY SPEED (IDLE):	1800 rpm