

ROOF SEALANT



PRODUCT DESCRIPTION

One component professional all weather roof sealing based on synthetic rubber, 280 ml capacity.

APPLICATION

Roof sealing (profiled metal sheets, ceramic and concrete tiles), gutters, risers, flashings, roof windows, skylights, balustrades, chimneys.

CAPACITY

| Index | Capacity |
|--------------|----------|
| | [ml] |
| PSILDEK280ML | 280 |

HOW TO USE

The surfaces to be sealed must be clean and degreased. Application temperature from + 5°C to + 40°C. Smooth the grout within 10 minutes of application. Carry out a test for plastics. Do not use in places permanently immersed in water or under constant water pressure. Do not use for polystyrene.

MAIN ADVANTAGES

- Flexible and durable
- On wet and dry surfaces
- Painting allowed
- UV resistant
- Resistant to weather conditions
- Mold resistant

PROPERTIES

Permanently plastic and elastic in the range from -25°C to + 100°C. It protects against the ingress of water. Paintable after hardening. Does not cause corrosion. Adhesive to smooth and porous materials. It does not contain silicone. Resistant to harsh weather conditions.

TECHNICAL DATA

Application temperature: +5°C to +40°C

Working time: 10 min

Curing time: up to 4 days

Thermal resistance after hardening: -25°C to + 100°C

Water absorption: 0%

Color: transparent